



# WATERPROOFING

## MiraDRAIN® Product Guide

| Product                 | Description   | Flow Rate  | Core          | Fabric Description                            | Fabric Apparent Opening Size* | Fabric Water Flow Rate  | Thickness | Compressive Strength |
|-------------------------|---|------------|---------------|---|-------------------------------|-------------------------|-----------|----------------------|
| <b>MiraDRAIN 2000</b>   | Intermediate-flow, low compressive-strength, shallow depths not exceeding 10 feet   | 18 gpm/ft. | Polypropylene | Nonwoven filter fabric                        | 40 Sieve                      | 110 gpm/ft <sup>2</sup> | 0.40"     | 11,000 psf           |
| <b>MiraDRAIN 6000</b>   | High-flow, high-compressive strength  | 21 gpm/ft. | Polypropylene | Nonwoven filter fabric                        | 40 Sieve                      | 140 gpm/ft <sup>2</sup> | 0.40"     | 15,000 psf           |
| <b>MiraDRAIN 6000XL</b> | High-flow, high-compressive strength, can be installed horizontally in planters   | 21 gpm/ft. | Polypropylene | Nonwoven filter fabric meeting AASHTO M288-06 | 70 Sieve                      | 110 gpm/ft <sup>2</sup> | 0.40"     | 16,500 psf           |
| <b>MiraDRAIN 6200</b>   | High-flow, high-compressive strength, Polymeric Sheet - prevents die-cutting of waterproofing membrane  | 21 gpm/ft. | Polypropylene | Nonwoven filter fabric                        | 40 Sieve                      | 110 gpm/ft <sup>2</sup> | 0.40"     | 15,000 psf           |
| <b>MiraDRAIN 6200XL</b> | High-flow, high-compressive strength, can be installed horizontally in planters, Polymeric Sheet - prevents die-cutting of waterproofing membrane | 21 gpm/ft. | Polypropylene | Nonwoven filter fabric meeting AASHTO M288-06 | 70 Sieve                      | 110 gpm/ft <sup>2</sup> | 0.40"     | 16,500 psf           |
| <b>MiraDRAIN 8000-P</b> | High-performance, chemical resistant  | 23 gpm/ft  | Polypropylene | Monofilament woven filter fabric              | 40 Sieve                      | 60 gpm/ft <sup>2</sup>  | 0.40"     | 21,000 psf           |
| <b>MiraDRAIN 9000</b>   | High-performance, high-strength   | 23 gpm/ft. | Polypropylene | Monofilament woven filter fabric              | 40 Sieve                      | 60 gpm/ft <sup>2</sup>  | 0.40"     | 21,000 psf           |
| <b>MiraDRAIN 9800</b>   | High-performance, high-strength   | 23 gpm/ft. | Polypropylene | Heavy-weight, nonwoven filter fabric          | 80 Sieve                      | 95 gpm/ft <sup>2</sup>  | 0.40"     | 21,000 psf           |
| <b>MiraDRAIN 9900</b>   | High-performance, very high-compressive strength  | 24 gpm/ft. | Polypropylene | Monofilament woven filter fabric              | 40 Sieve                      | 60 gpm/ft <sup>2</sup>  | 0.40"     | 33,000 psf           |
| <b>MiraDRAIN HC</b>     | High-flow, foundation or edge drain   | 30 gpm/ft. | Polypropylene | Nonwoven filter fabric                        | 40 Sieve                      | 110 gpm/ft <sup>2</sup> | 1"        | 9,500 psf            |
| <b>MiraDRAIN GR9400</b> | Horizontal green roof applications with moisture retention mat fabric   | 21 gpm/ft. | Polypropylene | Moisture retention filter medium              | 100 Sieve                     | 250 gpm/ft <sup>2</sup> | 1"        | 9,500 psf            |

\*AOS (Apparent Opening Size) - A higher Percent Opening Area will be less susceptible to long-term clogging.