



**NOTES:**

1. METAL SCUPPER BOX MUST HAVE CONTINUOUS SIDES, METAL FLANGE MUST BE CONTINUOUS WITH ROUND CORNERS.
2. WATER CUT-OFF MASTIC MUST BE HELD UNDER CONSTANT COMPRESSION.
3. METAL SCUPPER FLANGE ON WALL MUST BE TOTALLY COVERED BY UNCURED ELASTOFORM FLASHING.
4. UNCURED ELASTOFORM FLASHING MUST OVERLAP WALL FLASHING 3" (8 cm) MIN.
5. A MIN. 2" (5 cm) FLASHING SPLICE IS REQUIRED PAST THE NAIL HEAD ON THE METAL FLANGE OF THE SCUPPER.

CCW MIRADRI 860/861 – TIE INTO EXISTING USING AS REQUIRED CCW-702 AND CCW-LM-800XL

CCW MIRADRAIN DRAINAGE COMPOSITE, CCW PROTECTION BOARD OR CCW-300HV

CCW-MIRADRI 860/861

EXISTING CCW-MIRADRI 860/861

CCW-CONTACT ADHESIVE

CCW-704 MASTIC, CCW-703V LIQUISEAL, CCW-201 OR CCW-LM-800XL

SECURE METAL FLASHING TO PREVENT MOVEMENT

FLASH UNDER METAL FLASHING WITH A STRIP OF MIRADRI 860

AS A MANUFACTURER OF CONSTRUCTION MATERIALS, CARLISLE, DOES NOT ASSUME RESPONSIBILITY FOR ERRORS IN DESIGN OR ENGINEERING. ARCHITECT OR OWNERS REPRESENTATIVE MUST VERIFY SUITABILITY OF DETAILS.

860-18A

OVERFLOW METAL SCUPPER



© 2016 CARLISLE CORPORATION